

D O N G H I A®

Please inspect all rolls before cutting
Client assumes full responsibility for wallcovering after it is cut.

This wallcovering is made especially for us, using the best materials available. Once installed all wallcoverings will change color as a result of exposure to light, oxidation and airborne pollutants. Donghia cannot therefore, warrant these papers against fading or color shifts in installation.

Should defects be detected, do not proceed; contact us immediately. No claims will be allowed for more than three strips. No claim for labor will be accepted.

It is always best to avoid installation during high humidity periods. Make sure walls are prepared and no mildew conditions exist. The most important recommendation from Donghia is to employ an experienced professional installer. It is recommended that the installer, if unfamiliar with this product, test one or two panels prior to installation to become familiar with its properties.

Please note: All recommendations given are based on experience and tests which are believed to be reliable. However, as the conditions of use are outside our control, the information is offered without guarantee.

Wall Preparation:

To ensure a beautiful result, proper preparation is necessary. The walls need to be clean, dry, smooth and structurally intact. Prepare and size the walls. Porous surfaces such as new construction or walls painted with water based or latex paints should be primed using a *flat oil-based primer sealer*. After allowing the primer to dry, the walls should be lined with a good grade of lining paper, which should be allowed to dry overnight. Lining is not required but can be used at the discretion of the paperhanger.

Paste:

The strips of wallcovering should be pasted one at a time using wheat paste or vinyl clear hang. The final choice of paste is the sole responsibility of the installer. Do not get adhesive or water on the face of the wallcovering.

Installation:

Wallcovering must be hung within thirty minutes after applying adhesive. Moisture may soak through to the front surface; this can easily be wiped away with a clean damp sponge. Do not scrub.

After applying adhesive to the back of the strip, do not fold. Roll the strip so the back of the strip makes contact at the top and bottom, ready to hang. Do not lay strips on top of one another after applying paste, or lay pasted surface of one over pasted surface of another strip. (Strips may become damaged when attempting to pull apart.)

Double pasting is recommended but do not soak the wallcovering excessively. It is very important to locate the match prior to trimming. Edges need to be pre-trimmed using one blade per cut. Strips should be lined up to match (join marks are provided for matching), double cut, and hung butt joined.

Questions: Regarding the installation or appearance of this wallcovering, please call your local representative, or call our client service department at **1 800 DONGHIA**